

PVS-2421

2U rackmount 4 PCI slot DVR hardware platform

FEATURE

- ◆ Industrial grade platform
- ◆ 19" 2U rack-mount chassis 482x442x88 mm
- ◆ Intel® Pentium® 4 or Celeron® processor 2.0 ~ 2.8 GHz in the mPGA478 package
- ◆ Intel 865 GV integrated graphics with up to 64 MB shared DDR memory
- ◆ 4 PCI expansion slots
- ◆ One slim DVD-RW and two swappable 3.5" HDD
- ◆ TYPE II CF socket x1, USB x4, RS-232 x1, RS-485 x1



◀ 2421

PVS-2420 & PVS-2421 Reference Table

SPECIFICATION

		
Model	PVS-2420	PVS-2421
Dimension	430 x 445 x 88 mm; 16.93" x 17.52" x 3.46"	482 x 442 x 88 mm; 18.98" x 17.4" x 3.46"
CPU	Intel® Pentium® 4 up to 2.8 GHz / Celeron® up to 2.8 GHz	
Chipset	Intel® 845GV	Intel® 865
Display	Up to 64 MB shared DDR memory (DVMT)	
System Memory	<ul style="list-style-type: none"> ■ Up to 2 GB DDR 200/266 SDRAM on two 184-pin DIMM sockets ■ ECC support 	
Ethernet	10 BASE-T/100 BASE-TX Fast Ethernet (Gigabit Ethernet optional)	
MIO	RS-232 x1, RS-232/422/485 x1	
Audio	AC '97 2.2	
USB	USB 2.0 x3 (2 in the front)	USB 2.0 x4 (2 in the front)
Power Supply	300 W, PFC	
Expansion Interface	4 PCI slots	
HDD	Internal HDD x4	■ Swappable HDD x2, Slim CD-RW/DVD-RW x1
SSD	N/A	Type II CF socket x1
Optional	Gigabit Ethernet; TV-out; SCSI extension module	

* Specifications are subject to change without notice.

* All trademarks, logos and brand names are the property of their respective owners.