

ACTI-3500

The World's First 2U SCSI-to-IDE RAID Server with 6 IDE Drives



Specifications

- ◆ **Computing Board**
Support various SBC boards
- ◆ **RAID Levels**
0, 1, 3, 5, 0+1
- ◆ **Data Transfer Rate**
High speed host interface up to 40MB/sec
- ◆ **Hot-swappable mobile rack**
For up to 6 IDE
- ◆ **Peripherals**
Support one Laptop type CD-ROM & FDD
- ◆ **Backplane**
Support 4 PCI slots
- ◆ **Power Supply**
Two 300W redundant modules with load-sharing feature
- ◆ **Cooling Fan**
Four 8cm ball-bearing fans (4x35.31CFM)
- ◆ **Operating Temperature Range**
0 to 45°C, 20-90%RH
- ◆ **Storage Temperature Range**
0 to 70°C, 5-95%RH
- ◆ **Dimension**
483(W) x 638(D) x 89(H) mm
19"(W) x 25.1"(D) x 3.5"(H)
- ◆ **Weight**
Gross: 20kg / 44lb
Net: 12.3kg / 27lb (without SBC & HDD)
- ◆ **Color**
Black

Features

- ◆ The world's first cost-saving 2U RAID server
- ◆ OS independent and no driver required
- ◆ Space saving system with up to 6 Ultra DMA IDE disks
- ◆ Intel® i960 Hardware-based RAID controller
- ◆ Ultra-wide SCSI host interface
- ◆ On-line Hot-spare and Hot-swap features and auto-rebuild
- ◆ Fax and pager event notification
- ◆ Lower cost per megabyte
- ◆ 300W redundant power supply provides secure and sufficient power for system
- ◆ PICMG backplane for SBC and add-on card expansion
- ◆ Compact EZDRV with Laptop type of CD-ROM and FDD