

# CETUS-3200

## 2U Cost Effective SCSI-to-IDE RAID Subsystem

### Features

- ◆ The world's first cost-saving 2U RAID
- ◆ Space saving system with up to 6 ATA 33/66 IDE disks
- ◆ Optional dual host support
- ◆ OS independent and no driver required
- ◆ Intel® i960 Hardware-based RAID controller
- ◆ Ultra-Wide SCSI host interface
- ◆ On-line hot spare and swappable features and auto-rebuild
- ◆ FAX and pager event notification
- ◆ Lower cost per megabyte
- ◆ Backplaned disk channels, no disks cabling required
- ◆ 300W redundant power supply provides secure and sufficient power for system



### Specifications

- ◆ **RAID Levels**  
0, 1, 3, 5, 0+1
- ◆ **Data Transfer Rate**  
High speed host interface up to 40MB/sec
- ◆ **Host swappable modules**  
For up to 6 IDE HDDs
- ◆ **Memory Cache**  
16-128MB (built-in 32MB)
- ◆ **Power Supply**  
Two 300W redundant modules with load-sharing feature
- ◆ **Cooling Fan**  
Four 8cm ball-bearing fans (4x35.31CFM)
- ◆ **Operating Temperature Range**  
0 to 45°C, 20-90%RH
- ◆ **Storage Temperature Range**  
0 to 70°C, 5-95%RH
- ◆ **Dimension**  
483(W) x 457(L) x 89(H) mm  
19"(W) x 17.9"(L) x 3.5"(H)
- ◆ **Weight**  
Gross: 18kg / 39.6lb (without HDD)  
Net: 12kg / 26.45lb (without HDD)
- ◆ **Color**  
Black