

CETUS-3400

The Most Cost-effective SCSI-to-IDE RAID Subsystem

Features

- ◆ Fully integrated system backplane, allows cable-less connection to all HDDs for better performance and reliability
- ◆ Two Hot-swappable fans, located at the back for easy maintenance
- ◆ Front-side-loading Hot-swappable redundant power supply
- ◆ Drive interface: ATA66
- ◆ Host interface: U2 SCSI and upgradeable to fibre channel
- ◆ Hot-spare, Hot-swap, and on-line auto-rebuild function support
- ◆ Auto failure detection, and pager & fax event notification
- ◆ OS Independent and host transparent, no driver is required
- ◆ Key-lock Hot-swappable mobile rack with LEDs to indicate HDD status



Specifications

- ◆ **RAID Controller**
Equipped with Intel® i960 chipset based, Ultra2 SCSI-ATA 66 IDE RAID controller
- ◆ **Hard Disk Drive Bay**
Eight Hot-swappable IDE HDDs
- ◆ **Cooling Fan**
Two 8cm ball-bearing fans
- ◆ **Power Supply**
Two 300W redundant power supply
- ◆ **Raid Level**
Support Raid 0, 1, 3, 5 and 0+1
- ◆ **Data Transfer Rate**
80MB/sec
- ◆ **Operating Temperature Range**
5 to 45°C, 20-90%RH
- ◆ **Storage Temperature Range**
0 to 70°C, 5-95%RH
- ◆ **Dimension**
482(W) x 431(L) x 132.6 (H) mm
19"(W) x 16.9(L) x 5.2" (H)
- ◆ **Weight**
Gross: 24.5kg/54lb (without HDD)
Net: 16.6kg/36.5lb (without HDD)
- ◆ **Color**
Black